

RS Calibration Calibration and Repair Service Serial No: 019160

Cert No: 1792986 Cal Date: 20 Mar 2023

DPN 175 Lammas Road, Corby, Northants, NN17 9RS

Calibration Certificate Do Not Destroy

Calibration Certificate Attached: 1792986

OD ref: 1217662782

Mitutoyo 150 mm Digital Caliper

first

IMPORTANT INFORMATION

Simply detach the label in the top right hand corner of the new front sheet and apply to your instrument as required.



Calibration
Calibration and Repair Service Serial No: 2A345G02

123456 Cert No: Cal Date: 01 May 2014

Calibration Recal Due:

DPN 175 Lammas Road, Corby, Northants, NN17 9RS

For Re-Calibration of your unit please email: calibration.uk@rs-components.com or call us on 01536 405545 to arrange free collection. Please quote serial number when returning.





CERTIFICATE OF CALIBRATION

Issued by: RS Components Ltd

Date Issued:

20 Mar 2023

Certificate No. 1792986





0310

R5 Calibration

Calibration and Repair Service

DPN 175, Lammas Rd, Weldon Industrial Est Corby, Northants, NN17 9RS

Tel: 01536 405545 Fax: 01536 401590 Page 1 of 3 Pages



Stefan Sabadi

Client

TOTAL LABORATORY SERVICES LTD

BLANDFORD FORUM

DORSET DT11 8ST

Instrument

Mitutoyo 150 mm Digital Caliper

Serial No.

019160

Client Reference

N/A

Procedure ID.

D02_1150_# Rev. P3(Code: Mi)

Date of Calibration

20 Mar 2023

Remarks

This certificate reports recorded values for the instrument 'As Received'.

Uncertainties

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor k = 2, providing a level of confidence of approximately 95%. The uncertainty evaluation has been carried out in accordance with UKAS requirements.

For certificate statements of conformity see Appendix SCQAR 533

The following calibration results relate only to the items defined above.

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service.

It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes

This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

CERTIFICATE OF CALIBRATION

UKAS Accredited Calibration Laboratory No. 0310

R5 Calibration

Calibration and Repair Service

Certificate No.

Page 2 of 3 Pages

Environment

The ambient temperature and relative humidity throughout the calibration were (20 \pm 2) °C and (40 \pm 20) %RH respectively.

Calibration

The instrument was held in a temperature controlled environment for a period of not less than 4 hours prior to calibration which was performed using gauge blocks, length bars and in accordance with RS Calibration procedure MLCP01. The results are compared with the tolerances specified by SCQAR532_RS Standard Limits For Calipers.

Flatness of external faces:

0.004 mm

Parallelism of measuring jaws:

Internal

0.011 mm

External

At 1 mm

At 140 mm

0.013 mm 0.009 mm

No limits are applied to the above values.

Measurement uncertainties for the above values. ± 0.002 mm

Calibration of Gauge

	Tested Size	Limits	Gauge Reading	Deviation	Measurement Uncertainty
	(mm)	(mm)	(mm)	(mm)	(mm)
External	0.00	+/- 0.02	0.00	0.00	+/- 0.012
	31.20	+/- 0.02	31.19	-0.01	+/- 0.012 #
	61.40	+/- 0.02	61.38	-0.02	+/- 0.012 #
	92.60	+/- 0.02	92.58	-0.02	+/- 0.013 #
	123.80	+/- 0.03	123.78	-0.02	+/- 0.014 #
	150.00	+/- 0.03	149.98	-0.02	+/- 0.015 #
Internal	50.00	+/- 0.04	50.04	0.04	+/- 0.012 #
Step	50.00	+/- 0.04	50.01	0.01	+/- 0.012
Depth Rod	50.00	+/- 0.04	50.00	0.00	+/- 0.012
Zero re-check				0.00	

Calibrated by: SRS

CERTIFICATE OF CALIBRATION

UKAS Accredited Calibration Laboratory No. 0310

R5 Calibration

Calibration and Repair Service

Certificate No.

Page 3 of 3 Pages

Reported values not annotated.

The instrument passed the stated specification, due allowance having been made for the uncertainty of measurement which carries no implication regarding the long term stability of the instrument.

Reported values annotated with a

The measured result is a conditional pass to the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the stated level of confidence.

END OF CALIBRATION

Appendix SCQAR533 Certificate Statements of conformity

RS Components is standardising how it reports conformity across all disciplines in line with requirements within ISO/IEC: 17025:2017.

Where the laboratory reports a statement of conformity to a specification, guidance has been drawn on reporting structure and decision rules from ILAC document series ILAC-G8:09/2019.

Unless otherwise instructed by you the Customer, acceptance limits applied are derived from the manufacturers specification or applicable standard (e.g. DIN, EEC, BS etc.) or where applicable: SCQAR532 RS Standard Limits for Calipers, available on request.

The statements found on this certificate produced by RS Components Laboratory are as follow:

1) Reported values with No Annotation:

The instrument **passed** the stated specification, even with allowance having been made for the uncertainty of measurement, which carries no implication regarding the long-term stability of the instrument.

2) Reported values annotated with "#"

The measured result is a **conditional pass** to the limit but by a margin less than the measurement uncertainty, it is therefore not possible to state compliance based on the stated level of confidence.

3) Reported values annotated with "##"

The measured result is a **conditional fail** to the limit but by a margin less than the measurement uncertainty, it is therefore not possible to state compliance based on the stated level of confidence.

4) Reported values annotated with "###"

The measured result failed the stated specification, even with allowance having been made for the measurement uncertainty.

