

# \*\*Calibration Certificate\*\* Do Not Destroy

Calibration Certificate Attached: 1844885


OD ref: 1229876485

Plunger Dial Indicator

first

# IMPORTANT INFORMATION

Simply detach the label in the top right hand corner of the new front sheet and apply to your instrument as required.



DPN 175 Lammas Road, Corby, Northants, NN17 9RS

For Re-Calibration of your unit please email: calibration.uk@rs-components.com or call us on 01536 405545 to arrange free collection. Please quote serial number when returning.



# CERTIFICATE OF CALIBRATION

Issued by: RS Components Ltd

Date Issued:

22 Jan 2024

Certificate No.

1844885





0310

# **R5** Calibration

Calibration and Repair Service

DPN 175, Lammas Rd, Weldon Industrial Est Corby, Northants, NN17 9RS

Tel: 01536 405545 Fax: 01536 401590 Page 1 of 3 pages

6

Gary Chadwick

Client

TOTAL LABORATORY SERVICES LTD

**BLANDFORD FORUM** 

DORSET DT11 8ST

Instrument

Plunger Dial Indicator

Serial No.

**EAW557** 

Client Reference

N/A

Procedure ID.

D03\_1500\_# Rev. P6

Date of Calibration

22 Jan 2024

### Remarks

This certificate reports recorded values for the instrument 'As Received'.

### **Uncertainties**

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor k = 2, providing a level of confidence of approximately 95%. The uncertainty evaluation has been carried out in accordance with UKAS requirements.

For certificate statements of conformity see Appendix SCQAR 533 The following calibration results relate only to the items defined above.

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service.

It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes

This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

# **CERTIFICATE OF CALIBRATION**

UKAS Accredited Calibration Laboratory No. 0310

Certificate No. 1844885

Page 2 of 3 pages

# **R5** Calibration

Calibration and Repair Service

### **Environment**

The ambient temperature and relative humidity throughout the calibration were (20  $\pm$  2) °C and (40  $\pm$  20) %RH respectively.

### Calibration

The instrument was held within the temperature controlled laboratory for a period of not less than 4 hours prior to calibration which was performed using a DTI calibration tester and in accordance with RS Calibration procedure MLCP17.

The recorded results were compared with BS 907:2008 specification.

	Limit	Measured Value	
	(mm)	(mm)	
Repeatability :	0.002 0	0.000 0	
Discrimination :	0.003 0	0.000 0	

Interval of Reading	BS 907:2008 Limit (mm)	Maximum Deviation (mm)
Any 0.1 mm	0.005 0	0.003 0
Any half revolution	0.007 5	0.003 0
Any one revolution	0.010 0	0.004 0
Any two revolutions	0.015 0	0.004 0
Any larger interval	0.020 0	0.010 0

Uncertainty of Measurement :

e 0.002 mm

Calibrated By:- SEA

# **CERTIFICATE OF CALIBRATION**

UKAS Accredited Calibration Laboratory No. 0310

**R5** Calibration

Calibration and Repair Service

Certificate No.

1844885

Page 3 of 3 Pages

### Reported values not annotated.

The instrument passed the stated specification, due allowance having been made for the uncertainty of measurement which carries no implication regarding the long term stability of the instrument.

**END OF CALIBRATION** 

## **Appendix SCQAR533 Certificate Statements of conformity**

RS Components is standardising how it reports conformity across all disciplines in line with requirements within ISO/IEC: 17025:2017.

Where the laboratory reports a statement of conformity to a specification, guidance has been drawn on reporting structure and decision rules from ILAC document series ILAC-G8:09/2019.

Unless otherwise instructed by you the Customer, acceptance limits applied are derived from the manufacturers specification or applicable standard (e.g. DIN, EEC, BS etc.) or where applicable: SCQAR532 RS Standard Limits for Calipers, available on request.

The statements found on this certificate produced by RS Components Laboratory are as follow:

### 1) Reported values with No Annotation:

The instrument passed the stated specification, even with allowance having been made for the uncertainty of measurement, which carries no implication regarding the long-term stability of the instrument.

### 2) Reported values annotated with "#"

The measured result is a **conditional pass** to the limit but by a margin less than the measurement uncertainty, it is therefore not possible to state compliance based on the stated level of confidence.

### 3) Reported values annotated with "##"

The measured result is a **conditional fail** to the limit but by a margin less than the measurement uncertainty, it is therefore not possible to state compliance based on the stated level of confidence.

### 4) Reported values annotated with "###"

The measured result failed the stated specification, even with allowance having been made for the measurement uncertainty.

